

Applications: Walls



CEMENT

Wallcoverings » Advanced Wall Protection

Cement is a 137cm wide wall protection with a woven look that's resistant to impact, chemicals, and abrasion. Available in 8 hues of grey

Bleach Cleanable	✓ Easy Clean	Extended Warranty
✓ Extreme Durability	✓ High Stain Resistance	✓ Ultra Performance
Description	Check out the videos to see for yourself how Advanced Wall Protection performs -	

service, transportation and more.

Composition	Extra thick vinyl face on a heavy polyester / cotton knit fabric backing

Environmental Info	Formaldehyde free	
	Heavy metals free	
	Perfluorooctanoic acid free	

No solvent inks

Low VOC emissions. Any VOCs dissipate quickly (faster than paint) through normal ventilation and have no recognized adverse impact on indoor air quality.

Impact, Abrasion, Cleanability - or check out the brochure in the DOWNLOADS The technical innovation of P3TEC is a beautiful wall protection collection with three key advantages - High Performance, Easy to Use, Beautiful Design. Bring the look of silk, linen and wovens to high traffic, high abuse areas in healthcare, food

Durability means products do not need to be replaced regularly due to wear and tear and being cleanable, vinyl products are ideal for helping keep commercial environments clean of bacteria.

Baresque will only deal with vinyl manufacturers that comply with applicable state and federal regulations, provide a factory that is safe and clean for its employees to work in, recycle scrap and inks during the manufacturing process to minimize waste related to production.

Pattern Repeat Size	N/A	
Roll Size	137cm. Trims to 122cm x 13.7m Available by the FULL ROLL ONLY	
Fire Rating	Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.	
	The result achieved was: Classification - Group 2 Specific Extinction - Less than 250m²/kg	



CEMENT

Wallcoverings » Advanced Wall Protection

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

Suggested Installation

Non reverse hang/overlap double cut.

Baresque recommends and supplies Roman brand adhesives and primers.

Care Instructions

1. Completion:

Immediately upon completion of installation, installer shall make sure that these products are cleaned and free of any layout marks, excess adhesive or surface blemishes. Remove excess adhesive with methods and materials recommended by the adhesive manufacturer.

2. Clean-Up and Routine Maintenance:

Rigid Profiles: For general cleaning, use disinfectant cleaner.

All Purpose Cleaner Heavy Duty: Use a clean, lint-free cloth and wipe clean. Do not use any abrasive cleaning cloths or sponges.

- 1. Spray products onto profile and wipe with a dampened cloth.
- 2. Repeat process if stain remains. If cleaning product residue remains, rinse with water.

Warranty

5-year warranty. Visit **baresque.com.au/warranty** for complete details.



Colour & Finish Options







P3T-60327 KEYSTONE



P3T-60328 SHALE



P3T-60329 BASALT



P3T-60330 COBBLESTONE



P3T-60331 STONE AGE



P3T-60332 ROCK CRYSTAL



P3T-60325 MINERAL